FONTAINE	FIFTH WHEEL	RANGE
IUIUINIIUL	III III UUIILLL	naiuul

RANGE	MATERIAL	USAGE	APPLICATION	IMPOSED (U) & D-VALUE T / KN	WEIGHT KG	HEIGHT OPTIONS MM (DIN 6)	LOW MAIN- TENANCE	SINGLE- POINT AUTOLUBE	AIR ACTIV— ATION	SINGLE SENSOR SAFETY CLIP	SENSOR SYSTEMS	HANDLE OPTIONS
150SP <sup>2</sup>	Pressed	Standard duty 2" on-road	Fit for Flexible haulage volume carriers using two and three-axle tractors.	20T / 152kN	From 113kg	138 / 148 161 / 185 210 / 230 257	×	<b>✓</b>	<b>/</b>	<b>/</b>	<b>~</b>	Standard with safety clip     Extended with safety clip     Interlock
3000	Cast	Medium duty 2" on-road & limited off-road	Fit for Long-distance haulage with silo, tank and volume carriers using both two and three-axle tractors.	20T / 150kN	From 120kg	138 / 148 161 / 185 210 / 230 257	×	<b>✓</b>	<b>✓</b>	<b>/</b>	<b>✓</b>	Standard with safety clip     Extended with safety clip     Interlock
3000LM	Cast	Medium duty 2" on-road & limited off-road	Fit for Long-distance haulage with silo, tank and volume carriers using both two and three-axle tractors.	20T / 152kN	From 120kg	138 / 148 161 / 185 210 / 230 257	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	Standard with safety clip     Extended with safety clip     Interlock
163CI	Cast	Heavy duty 2" on & off-road	Fit for HGV traffic and off-road terrain.	23T / 163kN	From 140kg	148 / 161 185 / 210 230 / 257	×	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	Standard with safety clip     Extended with safety clip     Interlock

## FONTAINE MOUNTING OPTIONS

RANGE	USAGE	APPLICATION	IMPOSED(U) & D-VALUE T / KN	WEIGHT KG	HEIGHT MM	AIR / MANUAL	SLIDE TRAVEL	150SP <sup>2</sup>	3000	3000LM	163CI	RP59	RP90	FHD
SLIDING 150SF	Medium duty 2" on-road & limited off-road	Fit for Long-distance haulage with silo, tank and volume carriers using both two and three-axle tractors.	20T / 152kN	119kg	35mm	Air / Manual	Slide travel 525/750/900mm Two-position 300/525mm	<b>/</b>	<b>✓</b>	<b>✓</b>	<b>/</b>	<b>✓</b>	<b>✓</b>	<b>/</b>
MOUNTING PLATE	Medium duty 2" on-road & limited off-road	Fit for Long-distance haulage with silo, tank and volume carriers using both two and three-axle tractors.	20T / 150kN	45kg / 50kg	22mm 40mm	_	-	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>~</b>
DIRECT MOUNT	Standard duty 2" on-road	Fit for Flexible haulage volume carriers using two and three-axle tractors.	20T / 150kN	40kg	140mm 160mm 200mm 230mm	_	_	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	×	×	×